

GT-Smart

Battery Operated Strapping Tool

Battery Strapping Tool with multiple modes to suit any application

- Soft program for fragile packages
- Push button tensioning
- Easy to use and simple to adjust. Perfectly balanced, it can be used for both vertical and horizontal strapping
- Brushless motor powered with the latest generation Li-ion battery
- Easy removable cover for fast maintenance
- Digital display with visible parameters (tension force, welding time, battery charge level)
- Electromechanical push button for welding action start
- Ergonomic handle with skidproof rubber
- Tensioning start push button

Specification

- Strap PP/PET
- Strap width 9-16mm
- Strap thickness 0.4mm-0.85mm
- Seal efficiency 75-85%
- Tension range max. 1800N
- Tension speed 14m/min
- Weight 3.7kg
- Battery Akkupower SP6
- 14.4V 1.5 Ah Li-ion
- Cycles per charge 200-400
- Charging time 15-30mins



Victoria

37 Latitude Boulevard
Thomastown VIC 3074
Australia
T (03) 9474 3800
F (03) 9464 1504

New South Wales

2/17-19 Daniel Street
Wetherill Park NSW 2164
Australia
T (02) 9756 5433
F (02) 9756 0511

Queensland

2/16 Yarraman Place
Virginia QLD 4014
Australia
T (07) 3865 6089
F (07) 3865 3799

W www.cpspackaging.com
E info@cpspackaging.com

SIAT
H. J. HALLIS GROUP

CPS
The Whole Package