

AUTOMATIC STRAPPING MACHINE



YG-305 N

Victoria

37 Latitude Boulevard
Thomastown, VIC 3074
Australia

T (03) 9474 3800

F (03) 9464 1504

New South Wales

2/17-19 Daniel Street Wetherill
Park, NSW 2164 Australia

T (02) 9756 5433

F (02) 9756 0511

Queensland

2/16 Yarraman Place
Virginia, QLD 4014 Australia

T (07) 3865 6089

F (07) 3865 3799

Y8
GEN

AUTOMATIC STRAPPING MACHINE



YG-305 N

YG-305 N	SPECIFICATIONS
Model	YG-305 N Automatic Strapping Machine
Power Source	1Phase/220V/50-60HZ/0.6KW
Packing Speed	56path/min
Tension Force	0-45kg
Hot-adhering Position	Bottom
Table Height	850mm
Feed pp Straps	Auto feed pp straps
Frame	1. Standard Size: W500mm x H400mm (inner size) 2. Material: Iron frame (it's possible to customize size)
Applicable Strap	W5-9mm, D(0.5-0.8)mm
Applicable Strap Spool	Inner Diameter: 210mm
Packing Type	Parallel 1~several, manual packing, foot switch
Electrical Configuration	PC board control Button Switch: French "TE", Middle Relay: French "Schneider", Motor: Chinese "MEIWA" DC motor, Sensor Switch and Proximity Switch: German "P+F"
Machine Dimensions	L830mm × W700mm × H1385mm
Noise	≤75DB
Environment Condition	Humidity≤98%, Temperature 0-40 ° C
Bottom Adhesion	Adhesive surface≥90%, adhesive width≥20%, deviation of adhesive position≤2mm