

AUTOMATIC STRAPPING MACHINE



YG-305P

Victoria

37 Latitude Boulevard
Thomastown, VIC 3074
Australia

T (03) 9474 3800

F (03) 9464 1504

New South Wales

2/17-19 Daniel Street Wetherill Park,
NSW 2164 Australia

T (02) 9756 5433

F (02) 9756 0511

Queensland

2/16 Yarraman Place
Virginia, QLD 4014 Australia

T (07) 3865 6089

F (07) 3865 3799

Y^{GEN}8

AUTOMATIC STRAPPING MACHINE



YG-305P

YG-305P	SPECIFICATIONS
Model	YG-305P unmanned strapping machine
Power Source	3Phase/220V, 380V/50-60HZ
Packing Speed	50path/minute
Tension Force	0-45kg
Hot-adhering Position	Bottom
Table Height	850mm
Frame	1. Standard Size: W650mm x H500mm (inner size) 2. Material: Iron frame (It's possible to customize size)
Applicable Strap	W5-9mm, D(0.45~0.55)mm
Applicable Strap Spool	Inner Diameter: 210mm
Packing Type	Parallel 1~several; photoelectric control, Manual Operation
Electrical Configuration	PC board control +PLC control German "SIEMENS" Button Switch: French "TE", Relay: French "Schneider" Sensor Switch and Proximity Switch: German "P+F" Motor: Taiwan "MCN", Chinese "MEIWA" L1350mm × W568mm × H1500mm
Machine Dimensions	L1500 × W700 × H1600mm
Packing Measurement	N.W: 210kg, G.W: 250kg
Weight	≤75DB
Noise	Humidity≤98%, temperature 0-40 °C
Environment Condition	Adhesive surface≥90%, adhesive width≥20%, deviation of adhesive position≤2mm
Bottom Adhesion	