

AUTOMATIC STRAPPING MACHINE



YG-312

Victoria

37 Latitude Boulevard
Thomastown, VIC 3074
Australia

T (03) 9474 3800

F (03) 9464 1504

New South Wales

2/17-19 Daniel Street Wetherill
Park, NSW 2164 Australia

T (02) 9756 5433

F (02) 9756 0511

Queensland

2/16 Yarraman Place
Virginia, QLD 4014 Australia

T (07) 3865 6089

F (07) 3865 3799

Y8
GEN

AUTOMATIC STRAPPING MACHINE



YG-312

YG-312	SPECIFICATIONS
Model	1Phase/220V/50-60HZ/0.6KW 40 path/min 0-45kg Bottom
Power Source	850mm
Packing Speed	Auto feed pp straps
Tension Force	1. Standard Size: W650mm x H500mm (inner size) 2. Material: aluminum alloy frame (it's possible to customize size)
Hot-adhering Position	W9-12mm, D0.5~0.8mm
Table Height	Inner Diameter: 210mm Parallel 1~several; manual packing, foot switch
Frame	PC board control, Button Switch: French "TE" Middle Relay: French "Schneider", Single Chip: Chinese "MEIWA", Motor: Chinese "MEIWA" DC motor, Sensor Switch and Proximity Switch: German "P+F"
Applicable Strap	
Applicable Strap Spool	L1180mm × W620mm × H1430mm
Packing Type	≤75DB
Electrical Configuration	Humidity≤98%, Temperature 0-40 °C Adhesive surface≥90%, adhesive width≥20%, deviation of adhesive position≤2mm
Machine Dimensions	
Noise	
Environment Condition	
Bottom Adhesion	