

AUTOMATIC CASE ERECTOR

YGC F-20TX



Victoria

37 Latitude Boulevard
Thomastown, VIC 3074
Australia

T (03) 9474 3800

F (03) 9464 1504

New South Wales

2/17-19 Daniel Street Wetherill Park,
NSW 2164 Australia

T (02) 9756 5433

F (02) 9756 0511

Queensland

2/16 Yarraman Place
Virginia, QLD 4014 Australia

T (07) 3865 6089

F (07) 3865 3799

Y^{GEN}8

AUTOMATIC CASE ERECTOR



YGCF-20TX

YGCF-20TX	SPECIFICATIONS
Model	YGCF-20TX Case Erector
Supply Voltage	1PH 220V 50HZ (3PH optional)
Machine Weight	G.W 700kgs/N.W 660kgs
Machine Size	L2425 × W1855 × H1300mm
Worktable Height	650mm (standard) – 1000mm (maximum, customer-made)
Tape	Bopp tape or kraft paper tape
Tape Size	4.8 – 7.2cm wide
Power Installed	0.4KW
Air Supply	6 bar, free from water and oil
Electrical Enclosure	IP54
Noise Level	≤75DB4
Operating Environment	Humidity ≤98%, Temperature -10 °C ~ 40 °C
Working Speed	0-12 case/min
Carton Size	L250 – 530 x W150 – 400mm x a) H225 – 600mm (H+ W/2, after folding and sealing the bottom flap), b) H150 – 400mm (the machine can be custom-made for bigger size)
Main Electrical and Pneumatic Parts	PLC: “Siemens”, Touch screen: “Siemens”, Contactor: “Schneider”, Switch mode power supply: “Schneider”, Motor: “Luson” or “SEW” (optional), Sensor: “P+ F”, Cylinder: “Airtac”, Vacuum generator: “Festo”, Suction cup: “Festo”
Packing Size	L2.5 x W1.22 x H1.75m